

Steel Truck Actuated Dock Leveler 113-1/4 In. x 88 In. x 27-1/2 In. 20000 Lb. Capacity Brown

MODEL RU-800-SCB-F

Loading Dock Equipment / Truck Actuated Dock Levelers

PRODUCT OVERVIEW

This is a fully automatic loading ramp where there is no dock attendant needed. It is a recessed unit with a standard pit. It consists of a lift by-pass for safety and toe guards on each side. As the truck backs against the twin actuating arms (bumpers) it pushes the carriage back. The dock and trailer must be raised for this process to work. As the carriage goes back the deck goes up. When the carriage bumpers contact the dock, the deck floats down to rest on the trailer. When the truck pulls out, the deck returns to level supported position automatically.

KEY FEATURES

- Fully-automatic loading ramp where no dock attendant needed
- Recessed unit with a standard pit for ideal use
- Consists of a lift by-pass and toe guards on each side for optimal safety
- Deck returns to level supported position automatically

CORE PRODUCT DATA

ASSEMBLED WEIGHT
2475 lbs

ASSEMBLED SIZE
88" W x 113.25" L x 27.5" H

SHIP WEIGHT
2475 lbs

PACKAGE 1 SIZE
88" W x 108" D x 30" H

COLOR / FINISH
Brown

FREIGHT TYPE
LTL Loose

AVAILABILITY Please Contact Vestil for Current Availability

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	20,000
Molded Bumper Width (in.)	5
Molded Bumper Height (in.)	16
Molded Bumper Depth (in.)	2
PSI Checker Plated Deck	55,000
Service Range Above Dock (in.)	12
Service Range Below Dock (in.)	8
Long Lip (in.)	12 (extends 6-1/2 (in.) into truck)
Installation Method	Recessed Pit
Platform Type	Treadplate
Platform Thickness (in.)	1/4
Pit Width (in.)	74
Pit Length (in.)	86-1/2
Pit Depth (in.)	28

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=2>