

# Shutter Mounted Exhaust Fan 12 In. Blade Diameter Silver

**MODEL SME-12**

Facilities Maintenance / Shutter Mounted Exhaust Fans

## PRODUCT OVERVIEW

The shutter mounted exhaust fan offers inside-building installation only with vents outside. Eliminate need for external framing and shutter. Ideally suited for thin wall buildings. This fan is totally enclosed and permanently lubricated. Pull chain switch. No cord. Junction box provided for direct wiring. Meets OSHA standards.

## KEY FEATURES

- Shutter mounted exhaust fan eliminates the need for external framing and shutter
- Includes a 1/12 Horsepower motor with 115 voltage 1 phase 1.1 Amps power supply
- Fan is completely enclosed and permanently lubricated for maximum efficiency
- Includes a junction box for direct wiring in order to meet OSHA 1910 212(a)(5) standards

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**16 lbs**

**ASSEMBLED SIZE**  
**15.1875" W x 8.5" L x 15.1875" H**

**SHIP WEIGHT**  
**16 lbs**

**PACKAGE 1 SIZE**  
**16" W x 17" D x 11" H**

**COLOR / FINISH**  
**Silver**

**FREIGHT TYPE**  
**Parcel**

**AVAILABILITY** Quote Required - Please Contact Sales

**QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                      |                |
|----------------------|----------------|
| Blade Diameter (in.) | 12             |
| Motor Horsepower     | 1/12           |
| Amps High            | 1.1            |
| CFM High             | 825            |
| CFM Medium           | 710            |
| CFM Low              | 560            |
| Voltage/Phase        | 115V/1PH       |
| OSHA                 | 1910.212(a)(5) |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Johnson City, TN 37615

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES

See the live product page for current documents and downloads.



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=121>